



## Ferrule style high speed fuse links

FWP-10A14FI

UPC:051712510738

**Dimensions:** 

Height: 32 MMLength: 52 MMWidth: 15 MM

Weight:.012 KG

Warranties:

· Not Applicable

**Specifications:** 

• Type: FWP, Ferrule style

 Application: DC common bus, DC drives, power converters/rectifiers, reduced voltage starters

Amperage Rating: 10A

 Voltage Rating: 690 Vac (IEC), 700 Vac (UL), 800 Vdc (5-50A)

 Interrupt Rating: 200kA ac RMS Symmetrical, 50kA at 300 Vdc

Fuse Indicator: With IndicatorPackaging Type: Standard

 Used With: Finger safe holders/blocks and striker

• Current Rating: 15A

• Pre Arc (I2T): 4

• Clearing (I2T): Clearing at Rated voltage: 32

Diameter: 14 MMMaterial: Ceremic

Color: WhiteClass: aR

• Connection: Ferrule end X ferrule end

• Watt Losses: 5.5W

• Mounting: Fuse holder and blocks



• Quantity: 10

• Fuse Size: 14 x 51 mm

Supporting documents: No Data

## **Certifications:**

CSA CertifiedUL Recognized

## **Product compliance:**

CE Marked

© 2016 Eaton. All rights reserved.