

Rittal – The System.

Faster – better – everywhere.

FlatBox – DK 7507.000

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



FlatBox – DK 7507.000

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Version: with 19" mounting rails

Description: For flexible use as a wall-mounted or floor-standing enclosure.

Benefits: Tool-free quick mounting
System accessories on the open 19" frame

Material: Carbon steel
Viewing window: Single-pane safety glass, 3 mm

Surface finish: Powder-coated

Color: RAL 7035

Supply includes: Flat-packed enclosure
1 wall section
2 basic supports
2 roof/base plates, with cut-outs for cable entry via brush strips
2 side panels, lockable
1 glazed door, lockable, security lock 3524 E, door catch freely selectable
Connection components for tool-free, fast assembly
Grounding kit for system-compatible grounding of all enclosure parts
19" profile rails

Note: Max. installation depth: Depth - 58 mm to rear panel
Max. distance between two 19" levels: Depth - 104 mm

Base material: Carbon steel

Product features

| | |
|--|---|
| Dimensions: | Height: 358 mm (14 ") Width: 600 mm (24 ") Depth: 400 mm (16 ") |
| Installation height for components: | 6 U (6 U) |
| Packaging unit: | 1 pc(s). |
| Weight/packaging unit: | 17.84 kg (39.3 lb.) |
| EAN: | 4028177551398 |
| Customs tariff number: | 94032080 |
| ETIM 6.0: | EC002500 |
| ETIM 5.0: | EC002500 |
| eCl@ss 8.0/8.1: | 27180208 |
| eCl@ss 7.0/7.1: | 27180208 |
| eCl@ss 6.0/6.1: | 27180208 |
| eCl@ss 5.1/5.1.4: | 27180204 |
| Product description (long): | DK FlatBox, WHD: 600x358x400 mm, 6 U, with 482.6 mm (19") mounting angles |