


1

NOTES:
1. IDENTIFICATION: VERTICAL, (20) 5-20R
120V / 20A / SINGLE-PHASE POU

3. DIMENSIONS IN PARENTHESES ARE METRIC (mm).
4. SURGE SUPPRESSION UP TO 330V OR 720 JOULES.
5. UL® & c-UL® LISTED 1950.
6. RoHS COMPLIANT.

9. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.



MODEL FILENAME			09V098YM/01.PRT		
CAD FILENAME/LAYERS			09V098YM_DC/01A.PRT		
PANDUIT CORP TINLEY PARK, ILLINOIS					
VERTICAL, (20) 5-20R POWER OUTLET UNIT CUSTOMER DRAWING					
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:			UNLESS OTHERWISE SPECIFIED,		
[INCHES]		[METRIC - MILLIMETER]	ANGLE		
X.X	+/- 0.03	X.X	+/- 0.8		
X.XX	+/- 0.015	X.X	+/- 0.4		
X.XXX	+/- 0.005	X.XX	+/- 0.13	+/- 1°	
			ALL DIMENSIONS ARE GIVEN IN		
			INCHES, THIRD ANGLE PROJECTION		
DRAWN BY		MAT'L:		SCALE	
MRWA				NONE	
DATE				DRAWING NO.	
10-26-11				09V098YM	
CHK'D				DWG	
KRKE				B	
				SIZE	