

Rittal – The System.

Faster – better – everywhere.

Top-mounting module for TS – TS 8801.755

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Top-mounting module for TS – TS 8801.755

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description: As a cable routing compartment for cable infeed from above or for power distribution using busbar systems across bayed enclosures. The standard TS roof plate is used to blank off the top of the enclosure.

Material: Carbon steel, 1.5 mm

Surface finish: Spray-finished, textured paint

Color: Similar to RAL 7035

**Protection category
IP to IEC 60 529:** IP 55

**Protection category
NEMA:** NEMA 12

Mounting tip: The top baying cover cannot be fitted

Supply includes:
Frame module
2 trim panels front/rear
8 retainers with automatic potential equalization
4 threaded rods with transportation eyebolts

Product features

Suitable for: Enclosure type: TS
Width: 1000 mm (39 ")
Depth: 600 mm (24 ")

Dimensions: Height: 200 mm

Packaging unit:	1 pc(s).
Weight/packaging unit:	16.4 kg (36.2 lb.)
EAN:	4028177250505
Customs tariff number:	94039010
ETIM 6.0:	EC000744
ETIM 5.0:	EC000744
eCl@ss 8.0/8.1:	27182405
eCl@ss 7.0/7.1:	27182405
eCl@ss 6.0/6.1:	27182405
eCl@ss 5.1/5.1.4:	27182402
Product description (long):	TS Top-mounting module, for TS, for WD: 1000x600 mm
Approvals	
Approvals:	UL + C-UL
Certificates:	EAC