



BURNDY Catalog Number
UPC Number
Description
Status

YA36L2TC38FX
 7818101504055
 HYLUG-450(1100/24)-3/8X1
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	4.24
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.27
B Length (in)	1.38
Pad Width (in)	1.74
E - in	1.00
Strip Length	1-3/8

General

Number of Holes	2
Product Description	Cu Tubing Hylug, 2 Holes with Inspection Window, 450 kcmil Flex, 600V-35kV, 3/8" stud, Standard, Compression, 0.40 in BCD, Brown

Conductor(s)

Flex (Class G) Size - Range	450 kcmil
Flex (Class H) Size - Range	450 kcmil
Flex (Class I) Size - Range	450 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	444.4 (1100/#24) DLO
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20,299
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175