


Locking devices

Complex environment locking devices

Product description

2-pole, 3-wire grounding
30A, 480V/AC
NEMA L8-30



L8-30R

L8-30P

Plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
30	480	L8-30	Watertight	0.43-1.15" (10.9-29.2mm)	Y	□ L830PW	□ L830CW	•	•
			Watertight	0.43-1.15" (10.9-29.2mm)	BK	□ L830PWBK	□ L830CWBK	•	•
			Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ L830PY	□ L830CY	•	•

Receptacles

Rating A	V/AC	NEMA	Description	Color	Single receptacle catalog no.	
30	480	L8-30	Watertight	Y	□ L830RW	•
			Watertight	BK	□ L830RWBK	•



9965PY

Complex environment locking devices

Product description

3-pole, 3-wire non-grounding
20A, 125/250V/AC
Non-NEMA



Receptacle

Plug

Plugs & connectors

Rating A	V/AC	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	125/250	Watertight	0.36-0.84" (9.1-21.3mm)	Y	□ 9965PW	□ 7314CW	•	•
		Watertight	0.36-0.84" (9.1-21.3mm)	BK	□ 9965PWBK	□ 7314CWBK	•	•
		Severe duty	0.38-1.00" (9.7-25.4mm)	Y & BK	□ 9965PY	□ 7314CY	•	•

Receptacles

Rating A	V/AC	Description	Color	Single receptacle catalog no.	
20	125/250	Watertight	Y	□ 7314RW	•
		Watertight	BK	□ 7314RWBK	•

Dimensional information:


D-34-35

Specification information:

Watertight industrial plugs & connectors: D-38
Watertight industrial receptacles: D-39
Severe duty industrial plugs & connectors: D-40

Color information:

BK (Black), Y (Yellow)



(Black)

(Yellow)

Compliances, specifications and availability are subject to change without notice.



Indicates NAFTA compliant - Page Q-32



RoHS compliant - Page Q-32