

Rittal – The System.

Faster – better – everywhere.

► Hygienic Design Compact enclosure HD – HD 1306.600

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygienic Design Compact enclosure HD – HD 1306.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version: Roof slope 30° towards the front

Material: Housing and door: Stainless steel 1.4301 (AISI 304)
Mounting plate: Carbon steel
HD lock inserts: Stainless steel 1.4404 (AISI 316L)
Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600

Surface finish: Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm
Mounting plate: Zinc-plated
Seal: Blue, dyed (RAL 5010)

**Protection category
IP to IEC 60 529:** IP 66

**Protection category
IP to DIN 40 050-9:** IP 69K

**Protection category
NEMA:** NEMA 13
NEMA 4X

Supply includes: Housing of all-round solid construction
Door with fitted seal
Door catch on right, may be swapped to the left
Mounting plate

Base material: Stainless steel

Product features

Dimensions: Height (front): 430 mm (17 ")
Height (rear): 549 mm (22 ")
Width: 390 mm (15 ")

Depth: 210 mm (8.3 ")

Mounting plate:	Height: 355 mm (14 ") Width: 334 mm (13 ")
Number of cam locks:	1
Packaging unit:	1 pc(s).
Weight/packaging unit:	14.7 kg (32.4 lb.)
EAN:	4028177567603
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	HD Compact enclosure, WHD: 390x430(H1)x549(H2)x210 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal
Approvals	
Approvals:	UL + C-UL
Certificates:	DGUV EAC
Declarations:	Declaration of conformity