THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. PANDUIT WE I GHT POST FOR TAMPER COVER REMOVED FOR CLARITY PART NO. RESISTANT SCREW 2.8 LB/10 PCS NK6BX\*\*-AY 1270.0 g/10 PCS NOTES: 1. SEE CURRENT CATALOG FOR ADDITIONAL PART NUMBER SUFFIXES TO INDICATE COLOR AND OR PACKAGE QUANTITY. BREAKOUT AREA 2. SEE CATALOG FOR A COMPLETE LIST OF PARTS APPLICABLE FOR USE WITH (3 PLACES) THIS PART. 3. DIMENSIONS IN PARENTHESES ARE IN 3.28 METRIC. 0 [83.3] 4. ALSO INCLUDED WITH BOX: MOUNTING HOLES 1 - BOX BASE FOR #6 PAN HEAD I - BOX COVER 6.66 SCREW (11 PLACES) 2- PLTI.5I-C PAN-TY 2- MOUNTING SCREW 169.2 1- MOUNTING SCREW (USED TO 回 SECURE COVER TO BASE! 1.1 1 - LABEL/LABEL COVER 2- STRIP OF 3.00" X .75" FOAM TAPE FOR MOUNTING 5. BREAKOUTS DESIGNED TO ACCEPT LD3/LDP3 OR LD5/LDP5 LD10/LDP10 RACEWAY. 6. BASE MATERIAL THICKNESS: .090[2.29]. PAN-TY LOOP [32.0] FOR CABLE HOLD - DOWN (4 PLACES) NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WITH RESPECT TO ADHESIVE BOND PERFORMANCE. AMONG OTHER THINGS, THE CONDITIONS UNDER WHICH THESE MOUNTS MAY BE APPLIED AND/OR THE SURFACE TO WHICH THEY MAY BE APPLIED ARE BEYOND PANDUIT'S CONTROL. SIZE 4.70 DRAWING FILENAME [119.4] M02479BC\_DC029\_00A.PRT NETKEY 6 POSITION SURFACE MOUNT BOX CUSTOMER DRAWING I.I. NUMBER N/A CORP PRODUCT SPEC N/A TINLEY PARK, IL 60477 ALL DIMENSIONS ARE GIVEN IN INCHES, UNLESS OTHERWISE SPECIFIED. WORK INSTRUCTION N/A DIMENSIONAL TOLERANCES ARE: SCALE (.X) ±.03 (.XXX) ±.005 NONE THIRD ANGLE PROJECTION (.XX) ±.01 ANGLES ± 1° DRAWN BY MATERIAL: PART NO. JsP NK6BX\*\*-AY 5-2-07 JsP 5-2-07 RELEASED TO PRODUCTION 02479-029 DRAWING NO. ABS CHK 'D 02479-029 SUP REV DATE BY CHK DESCRIPTION ECN - R CUST ОТН