

Features

- Nylon Fitting
- Stainless steel mesh is corrosion resistant
- Neoprene bushing is oil and watertight

Ordering Information

| Description | Form Size | UPC | Catalog Number |
|--|-----------|--------------|----------------|
| 90° Male Thread, Liquidtight, for Insulated Cables | F4 | 783585335209 | CG81490NM |

Listings

UL Listed
CSA Certified



Online Resources

eCatalog

Specifications

| | |
|-----------------|-----------|
| Strand | Non-metal |
| Fittings | Nylon |
| Bushings | Neoprene |
| NPT Thread Size | 1 Inch |

Performance

Environmental

| | |
|------------------------|---|
| Flammability | UL 94HB (Strand grip), UL 94V-2(Fitting) |
| Hazardous Locations | Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C |
| Operating Temperatures | -30°F to +225°F (-34°C to +107°C) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.