



Powering Business Worldwide

pe.eaton.com

Time-Delay Fuse

BK/MDA-30-R

UPC:051712541008

Dimensions:

- **Height:** 1.25 IN
- **Length:** .25 IN
- **Width:** .25 IN

Weight:.4 LB

Warranties: No Data

Specifications:

- **Type:** Electronic
- **Application:** Electronic circuits
- **Amperage Rating:** 30A
- **Voltage Rating:** 250 Vac, 125 Vdc, 32 Vdc (self certified)
- **Interrupt Rating:** 1.5 kAIC at 250 Vac, 10 kICA at 125 Vac/dc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Response Time:** 60 min. maximum at 135%, 120 secs. maximum at 200%
- **Voltage Drop:** Typical: .110 mV
- **Melting (L2T):** Typical: 1096.7
- **Diameter:** .25 IN
- **Material:** Ceramic tube, nickel-plated brass endcaps
- **Connection:** Ferrule end X ferrule end
- **Quantity:** 100
- **Resistance:** Typical DC cold: .002465 ohms

Supporting documents:

- [MDA 30A BUSS TD BK 100 BOX -R](#)

Certifications: No Data

Product compliance:

- RoHS Compliant



- CE Marked

© 2016 Eaton. All rights reserved.