

# AHB

## WATER PIPE HEATING CABLE, FIXED RESISTANCE, PRE-TERMINATED



Each AHB cable consists of a tough XLPE inner insulation, a continuous ground braid and weather resistant PVC outer jacket. AHB units are activated and de-activated by an integral energy-saving thermostat. Each cable is UL Listed to Canadian Safety Standards and CSA Certified when used in accordance with instructions on water-filled metal or plastic pipes.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
AHB013 *	0.91m (3ft), 21 Watts	10	2.7kg (6lb)	0-13627-10950-6	
AHB016 *	1.83m (6ft), 42 Watts	10	3.2kg (7lb)	0-13627-10951-3	
AHB019 *	2.74m (9ft), 63 Watts	10	4.1kg (9lb)	0-13627-10952-0	
AHB112 *	3.66m (12ft), 84 Watts	10	4.5kg (10lb)	0-13627-10953-7	
AHB115 *	4.58m (15ft), 105 Watts	10	5.0kg (11lb)	0-13627-10954-4	
AHB118 *	5.49m (18ft), 126 Watts	5	3.2kg (7lb)	0-13627-10955-1	
AHB124	7.31m (24ft), 168 Watts	5	3.6kg (8lb)	0-13627-10956-8	
AHB130	9.14m (30ft), 211 Watts	5	4.1kg (9lb)	0-13627-10957-5	
AHB140	12.19m (40ft), 280 Watts	5	5.4kg (12lb)	0-13627-10958-2	
AHB160	18.29m (60ft), 420 Watts	5	6.8kg (15lb)	0-13627-10959-9	
AHB180	24.38m (80ft), 560 Watts	5	9.1kg (20lb)	0-13627-10960-5	
GTXAHB	Starter kit: 2 each of *'d above	-	8.6kg (19lb)	0-13627-10948-3	
GWJAHB	Jumbo kit: 5 each of *'d above	-	25.0kg (55lb)	0-13627-10949-0	

# FREEZE FREE®

## SELF-REGULATING, CUT-TO-LENGTH CABLE



**Freeze Free** – This self-regulating pipe heating cable automatically varies its heat output with changes in surrounding temperature. Freeze Free cable helps keep plastic and metal water pipes from freezing to -51°C (-60°F). A braided metal jacket provides an electrical ground as well as protection against damage in dry locations. Freeze Free cable is available on reels of 30.48 meters, 91.44 meters, and 152.40 meters (100 feet, 300 feet, and 500 feet) and can be cut to desired lengths per application. Pre-packaged lengths of 1.52 meters and 4.57 meters (5 feet and 15 feet) are also available. Cables are rated at 3 Watts per 0.30 meter (1 foot), 120 Vac at 10°C (50°F); 22.86 meters (75 feet) maximum circuit length, 0.91 meter (3 feet) minimum circuit length. Freeze Free cable is UL Listed to US and Canadian Safety Standards and CSA Certified.

**10802 Fused Plug and End Seal** – This connection kit provides the specially designed fused plug to connect one Freeze Free heater into an electrical outlet and a cable end seal which ensure safe and proper usage of the Freeze Free cable.

CATALOG NUMBER	DESCRIPTION	CTN QTY	CTN WGT	UPC	CERTIFICATIONS
2102	30.48m (100ft) reel Freeze Free	1	2.3kg (5lb)	0-13627-06895-7	
2302	91.44m (300ft) reel Freeze Free	1	5.9kg (13lb)	0-13627-06896-4	
2502	152.40m (500ft) reel Freeze Free	1	9.1kg (20lb)	0-13627-06894-0	
10802	Connection kit – clamshell pkg	10	1.4kg (3lb)	0-13627-10802-8	
10803	Connection kit – polybagged pkg	25	2.3kg (5lb)	0-13627-10803-5	
FFEC	End seals – 5 per bag	10	0.9kg (2lb)	0-13627-06946-6	
10805	1.52m (5ft) pre-packaged Freeze Free kit	5	1.8kg (4lb)	0-13627-10805-9	
10815	4.57m (15ft) pre-packaged Freeze Free kit	5	2.7kg (6lb)	0-13627-10815-8	
4102	30.48m (100ft) display: (1) reel; (10) 10802	1	3.6kg (8lb)	0-13627-06897-1	
4302	91.44m (300ft) display: (1) reel; (20) 10802; (10) EH38; (10) HCA	1	7.7kg (17lb)	0-13627-06898-8	
NPRO50	15.24m (50ft) pro pack: (1) reel; (3) 10803; (1) HCA	1	1.4kg (3lb)	0-13627-10798-4	
NPRO100	30.48m (100ft) pro pack: (1) reel; (6) 10803; (1) HCA	1	2.7kg (6lb)	0-13627-10799-1	