



Powering Business Worldwide

pe.eaton.com

Stud-Mount Fuse

FWP-30B

UPC:051712557832

Dimensions:

- **Height:** .001 IN
- **Length:** 35.039 IN
- **Width:** 2.362 IN

Weight:.22 LB

Warranties:

- Not Applicable

Specifications:

- **Type:** North American style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Voltage Rating:** 1400 Vac (FWS 8-15A), 2100 Vac (FWS 2-6A), 1000 Vdc (FWL/FWS 2-30A)
- **Interrupt Rating:** 200 kAIC Vac, 50 kAIC at 700 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Current Rating:** 30A RMS
- **Pre Arc (I²T):** 58
- **Clearing (I²T):** Clearing at 700V: 450
- **Connection:** Blade end X blade end
- **Watt Losses:** 9W
- **Mounting:** Stud

Supporting documents:

- [30AMP 700V AC SEMI-COND](#)

Certifications:

- UL Recognized
- CSA Certified

Product compliance:

- CE Marked



- RoHS Compliant

© 2016 Eaton. All rights reserved.