

Rittal – The System.

Faster – better – everywhere.

Pressure relief stoppers – SZ 2459.500

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Pressure relief stoppers – SZ 2459.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description: Pressure differences can cause condensation to form in sealed housings, especially when the housing is exposed to changing climatic conditions (e.g., with outdoor siting). The integrated sealing membrane largely prevents these pressure differences and the build-up of condensate, as well as protecting against the penetration of moisture from outside. Installation is in vertical surfaces, to protect against dirt.

Material: Polyamide

Color: Similar to RAL 9005

Technical specifications: Air permeability up to 120 liters/hour with a pressure difference of 70 mbar
Connection thread M12 x 1.5
For fitting in material thicknesses up to 4 mm

**Protection category
IP to IEC 60 529:** IP 66
IP 68

**Protection category
IP to DIN 40 050-9:** IP 69K

Supply includes: Incl. lock nut

Product features

Packaging unit: 5 pc(s).

**Weight/packaging
unit:** 0.02 kg (0 lb.)

EAN: 4028177516960

Customs tariff number:	39269097
ETIM 6.0:	EC002009
ETIM 5.0:	EC002620
eCl@ss 8.0/8.1:	27180715
eCl@ss 7.0/7.1:	27180715
eCl@ss 6.0/6.1:	27180715
eCl@ss 5.1/5.1.4:	27182092
Product description (long):	SZ Pressure relief stoppers
Approvals	
Certificates:	EAC