



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton Type MTE industrial control transformer

C0050E2AXXFB

UPC:786680031434

### Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

**Notes:** Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** No secondary fuse clips
- **Modification 2:** Factory-mounted two-pole primary fuse block for rejection type fuses
- **Primary Voltage:** 240 X 480V, 230 X 460V, 220 X 440V
- **Secondary Voltage:** 120/115/110V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** Industrial Control Transformer
- **Volt Ampere Rating:** 50 VA

### Supporting documents:

- [Industrial control transformers brochure](#)
- [dry-type distribution transformer-flex center line card](#)



- [Transformer distribution catalog, volume 2, tab 2](#)
- [Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Eaton Specification Sheet - C0050E2AXXFB](#)
- [Transformer consulting application guide](#)

**Certifications:**

- CSA Certified
- UL Listed
- cUL Certified

**Product compliance:**

- RoHS Compliant