



BURNDY Catalog Number	YGL34C29
UPC Number	781810220047
Description	250-500 TO 2-250 GRD GRI
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Length (in)	2.50
B Length (in)	0.75
General	
Product Description	Copper Compression Cross Grid Connector, 250 kcmil - 500 kcmil or 5/8" - 3/4" Ground Rod or # 5 - 6 Rebar, 2 AWG (Str.) - 250 kcmil
Prefilled (Oxide Inhibitor)	Y
Other	
Type of Oxide Inhibitor	Penetrox E
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467,IEEE 837
Conductor(s)	
Rod Size (Side A) - Range	5/8 in-3/4 in
Rod Size (Side B) - Range	N/A
Rebar Size (Side B) - Range	N/A
Copper Solid Size (Side A) - Range	N/A
Copper Str Size(Side B) - Range	2 AWG-250 kcmil
Copper Str Size (Side A) - Range	250 kcmil-500 kcmil
CopperSolid Size (Side B) - Range	N/A
Rebar Size (Side A) - Range	5 -6
Physical	
Type of Plating	Unplated
Plated (Yes or No)	N
Index Number	997,998
Product Material	Copper
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175

