

## Hinged and Open Front



Open Front Cover



Hinged Cover

## Applications:

Added environmental protection for Eaton's Crouse-Hinds control stations is now available from a patented "slip on" series of covers. Easy to install, these enclosures are available in hinged and open front styles, and are ideal for corrosive and adverse areas where product endurance is essential.

**Secured Access Hinged Cover**

- High moisture areas due to weather, steam, or wash down procedures.
- Areas where dirt, dust, mud, sand, etc. interferes with equipment operation.
- Prevention of accidental equipment operation.
- Instances requiring equipment lockout/tagout.

**Quick Access Open Front Cover**

- Areas requiring quick access to control device.
- Areas of high moisture from weather or dripping liquid.
- Prevention of accidental equipment operation.
- Areas with possible damage from bumping or banging.

## Features and Benefits:

- Clear UV stabilized Lexan polycarbonate plastic allows the end-user to see enclosed controls and is strong enough to withstand the rough treatment found in the industrial workplace.
- Downtime due to weather or accidental bumping is eliminated and plant shutdowns caused by inoperable or accidentally operated pushbutton devices are non-existent.
- Lockout/tagout capabilities conform to OSHA requirements and provides increased personnel safety.
- Quick and easy slip on installation requires no tools or interruption of service.
- Hinged cover provides superior sealing through heavy duty neoprene gaskets.
- Colored covers are available (e.g. red for emergency, yellow for fire alarm, etc.).
- Specific chemical-resistant covers available (may not be clear) - consult factory for minimum order quantity.
- Capability to engineer cover to fit any size device - consult factory.

## Hinged Covers

**Single Gang Application**

EDS(C) and EFD(C) control stations  
EFS(C) control stations  
MC(C) control stations  
FS(C) back box with cover assembly  
FD(C) back box with cover assembly  
EGF11 and EGF12 (Ground Fault)  
N2S(C) Krydon: 1 & 2 devices  
N2D(C) Krydon: 1 & 2 devices  
GHG432 control station

**Cat. #**

NC CH1  
NC CH1 EFS  
NC CH1 MC  
NC CH1 FS  
NC CH1 FD  
NC CH1 EGF 11  
NC CH1 N2S  
NC CH1 N2D  
NC CH1 GHG

**Single Gang (Long) Application**

EFD(C) (3 device)  
N2S(C) Krydon: 3 devices  
N2S(C) Krydon: 4 devices

**Cat. #**

NC CH1 3L  
NC CH1 N2S 3L  
NC CH1 N2S 4L

**Double Gang Application**

EDS(C) control stations  
EDSCM32: 2 gang tandem  
EDSCM33: 3 gang tandem  
FS(C) back box with cover  
FD(C) back box with cover  
EDSC378 - 3 gang tandem assembly

**Cat. #**

NC CH2  
NC CH2L  
NC CH3L  
NC CH2 FS  
NC CH2 FD  
NC CH1 MC3

## Open Front Covers

**Single Gang Application**

EDS(C) and EFD(C) control stations  
EFS(C) control stations  
MC(C) control stations  
FS(C) back box with cover assembly  
FD(C) back box with cover assembly  
EGF11 and EGF12 (Ground Fault)  
N2S(C) Krydon: 2 device assembly  
N2D(C) Krydon: 3 device assembly  
GHG432 control station  
GHG432 control station

**Cat. #**

NC CH1 QA  
NC CH1 EFS QA  
NC CH1 MC QA  
NC CH1 FS QA  
NC CH1 FD QA  
NC CH1 EGF QA  
NC CH1 N2S QA  
NC CH1 N2D QA  
NC CH1 GHG QA (clear)  
NC CH1 GHG QA RED (red)

**Single Gang (Long) Application**

EFD(C): 3 device control stations  
N2S(C) Krydon: 3 device assembly  
N2S(C) Krydon: 4 device assembly

**Cat. #**

NC CH1 3L QA  
NC CH1 N2S 3L QA  
NC CH1 N2S 4L QA

**Double Gang Application**

EDS(C) control stations  
EDSCM32: 2 gang tandem  
EDSCM 33: 3 gang tandem  
FS(C) back box with cover assembly  
FD(C) back box with cover assembly

**Cat. #**

NC CH2 QA  
NC CH2L QA  
NC CH3L QA  
NC CH2 FS QA  
NC CH2 FD QA

Custom covers can be supplied but must be accompanied by either a sample of the device to be covered or a copy of a drawing with all actual measurements of the device to be covered. Covers can also be color-coded. Consult factory.