

## Non-metallic • Easy, Push-in Installation



Save money with Arlington's non-metallic Black Button™ NM cable connectors. They're the lowest cost NM cable connectors on the market, and the fastest to install! Simply push the connector into the knockout, and you're done.

Listed for single or multiple cables, Arlington's Black Button connectors offer smooth, easy cable insertion into a single opening while exceeding UL and CSA pullout requirements.

- Removable, reusable
- 1/2", 3/4" and 1" trade sizes
- UL/CSA Listed

Our new 1/2" NM942 holds one or two cables, in two separate openings:

- One or two 12/2
- One or two 14/2, or one 12/2 and one 14/2

Use a screwdriver to remove NM942 from box. It's reusable!



1 Stauffer Industrial Park Scranton, PA 18517 800/233.4717 Fax 570/562.0646 www.aifittings.com



## Lowest Cost NM Cable Connector • Easy, Push-in Installation

- Listed for one or two cables
- Easy installation
- Smooth, easy cable insertion
- Secure hold on cable exceeds UL pullout tests

## For multiple cable installations:

Insert TWO cables together or individually into NM94, NM95 or NM96. Add a second cable without removing the first.





Push the NM cable connector into the knockout with light finger pressure.



2 Install one or two cables, fast! Push the NM cable(s) into the connector to the desired length.

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	DESCRIPTION/SIZE NM Cable Connector with SINGLE opening	KO SIZE	CABLE RANGES	UNIT PKG	STD PKG
NM94 NM940	05488 72156	3/8" 3/8"	1/2" 1/2"	One 12/2 to 10/2 One 14/2/2 Two 14/2 to Two 10/2 Two 14/3 to Two 12/3 One 14/2 and One 12/2 One 14/2 and One 10/2 One 12/2 and One 10/2 One 14/3 and One 12/3	250 100	1000 1000
NM95	10956	3/4"	3/4"	One 14/2 to 6/2 One 14/3 to 6/3 One 14/2/2 Two 14/2 to Two 10/2 Two 14/3 to Two 10/3 One 14/2 and One 12/2 One 14/2 and One 10/2 One 12/2 and One 10/2 One 14/3 and One 12/3	50	500
NM96	72158	1"	1"	One 4/3 to 8/3 One 6/2 to 4/2	25	250



1 Push connector into KO with light finger pressure.



1 Stauffer Industrial P Scranton, PA 18517 800/233.4717 Fax 570/562.0646 www.aifittings.com



2 Insert cable(s) into individual openings.





3 To remove from KO...Slip screwdriver under connector and twist.

KO	CABLE	UNIT	STD	
SIZE	RANGES	PKG	PKG	
1/2"	One or Two 14/2 One or Two 12/2 One 14/2 and One 12/2 One or Two 10/2	250	1000	



Distributed by	
Patented	