

# Rittal – The System.

Faster – better – everywhere.

## ► TopTherm air/air heat exchanger wall-mounted with controller – SK 3129.115

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TopTherm air/air heat exchanger wall-mounted with controller – SK 3129.115

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

**Color:** RAL 7035

**Protection category  
IP to IEC 60 529:** Internal circuit, IP 54

**Supply includes:** Complete unit ready for connection  
Plug-in terminal strip  
Floating fault signal contact in case of overtemperature

## Product features

**Specific thermal  
output:** 60 W/K

**Air throughput  
(unimpeded air flow):** External circuit at 50 Hz: 860 m<sup>3</sup>/h (506.2 cfm)  
External circuit at 60 Hz: 900 m<sup>3</sup>/h (529.7 cfm)  
Internal circuit at 50 Hz: 860 m<sup>3</sup>/h (506.2 cfm)  
Internal circuit at 60 Hz: 900 m<sup>3</sup>/h (529.7 cfm)

**Rated operating  
voltage:** 115 V, 1~, 50 Hz/60 Hz

**Dimensions:** Height: 950 mm (37 ")  
Width: 400 mm (16 ")  
Depth: 225 mm (8.9 ")

**Temperature control:** Electronic Control with Digital Display (factory setting +35°C)

**Temperature range:** Operation (environment): -5°C...+55°C

<b>Output per fan:</b>	At 50 Hz: 85 W At 60 Hz: 90 W
<b>Rated current (max.):</b>	per fan at 50 Hz: 0.65 A per fan at 60 Hz: 0.8 A
<b>Miniature circuit-breaker/fuse:</b>	2 A
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	21 kg
<b>EAN:</b>	4028177425118
<b>Customs tariff number:</b>	84158300
<b>ETIM 6.0:</b>	EC002514
<b>ETIM 5.0:</b>	EC002514
<b>eCl@ss 8.0/8.1:</b>	27180711
<b>eCl@ss 7.0/7.1:</b>	27180711
<b>eCl@ss 6.0/6.1:</b>	27180711
<b>eCl@ss 5.1/5.1.4:</b>	27180711
<b>Approvals</b>	
<b>Approvals:</b>	Approval overview UR + C-UR
<b>Certificates:</b>	EAC
<b>Declarations:</b>	Declaration of conformity