



# Xitanium LED Driver Outdoor Fixed (US)

## XITANIUM 10W 0.35A 28V 120V 60HZ OUTDOOR

Xitanium Outdoor LED Drivers are available in wattages from 40W to 150W for hard-wire integration into outdoor luminaires for the most rugged applications. These drivers operate to specification under wide temperature and electrical ranges to ensure reliability.

### Product data

Operating and Electrical	
Input Frequency	60 Hz
Total Harmonic Distortion IEC (Max)	20 %
Maximum Efficiency	85 %
Power Factor 100% Load (Min)	0.9
Output Current (Nom)	350 mA
Input Voltage (AC)	120 V
Input Current (Max)	100 mA
Input Power (Nom)	12.5 W
Output Power (Nom)	10 W
Output Voltage	2.8-28 V

  

Wiring	
Connector Type Input Terminals	Wago 250
Output Wire Length	152.4 mm
Input Wire Gauge	18
Output Wire Gauge	18

  

Temperature	
T-Ambient (Max)	60 °C

T-Ambient (Min)	-40 °C
T-Case Maximum (Max)	90 °C

  

Approval and Application	
EMI Standard	FCC 47 Subpart 18; Class A
Environmental Standard	UL Damp & Dry
Approval Marks	RoHS compliance UL certificate CSA certificate
Output Insulation	Yes

Product Data	
Full product code	871016319622000
Order product name	XITANIUM 10W 0.35A 28V 120V 60HZ OUTDOOR
EAN/UPC - Product	781087045145
Order code	913710267302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	80
Material Nr. (12NC)	913710267302
Net Weight (Piece)	0.134 kg

## Xtanium LED Driver Outdoor Fixed (US)

### Dimensional drawing

Product	D1	B2	C1	C2	A1	A2	B1
XITANIUM 10W	3.8	24.6	24.9	3.0	132.0	122.4	34.3
0.35A 28V 120V 60HZ OUTDOOR	mm	mm	mm	mm	mm	mm	mm

10W/0.35A-28V 120V OUTDOORS

