

# Rittal – The System.

Faster – better – everywhere.

## ▶ TS 8 Flange Mount Disconnect Floormount Enclosure – TS 8018.808

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# TS 8 Flange Mount Disconnect Floormount Enclosure – TS 8018.808 - TSFM634716XC

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

**Description:** Rittal's Floormount TS 8 combines the strength of unibody floormount enclosures with the flexibility of Rittal's revolutionary modular design. With its double door configuration and wide range of accessories, Rittal's Floormount TS 8 is sure to meet your UL Type 12 needs. Includes operator handle interlocking kit to securely lock most commercially available operator handles to enclosure and door latch.

**Material:** Enclosure frame: Carbon steel, 1.5 mm  
Roof: Carbon steel, 1.5 mm  
Door: Carbon steel, 2.0 mm  
Rear wall: carbon steel, 1.5 mm  
Mounting plate: Carbon steel, 3.0 mm

**Color:** RAL 7035

**Protection category  
IP to IEC 60 529:** IP 55

**Protection category  
NEMA:** UL Type 12

**Supply includes:** Enclosure frame with door(s)  
Roof plate  
Rear panel, detachable  
4 eyebolts

## Product features

**Dimensions:** Height: 1600 mm (63 ")  
Width: 1200 mm (47 ")  
Depth: 400 mm (16 ")

**Packaging unit:** 1 pc(s).

---

**Weight/packaging unit:** 163 kg (359.4 lb.)

---

**EAN:** 85551

---

## Approvals

---

**Approvals:** UL + C-UL

---