



BURNDY Catalog Number	BISR250DB
UPC Number	781810288061
Description	250-4/0 DIRECTBURIALUNIT
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Screw Size	5/8
Width (in)	1.18
Hex Size (Key)	5/16
Length (in)	6.70
Height (in)	2.17
Electrical	
Min Voltage Rating	600
General	
Number of Ports	2
Number of Screws	2
Product Description	In-Line Splice/Reducer, 2 Port, 4/0 AWG-250 kcmil, Al/Cu Rated
Conductor(s)	
Aluminum Size (Range)	4/0-250 kcmil
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	4/0 AWG-250 kcmil
Physical	
Type of Hardware	Aluminum
Installation Torque	360
Type of Plating	Unplated
Insulation Type	Plastisol
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
UL Listed	Y
CSA Certified	N
Rated for Direct Burial	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175