

WIRE MANAGEMENT

Direct Burial Roll-On Splice Sleeve

Easy-Splice™

ROS Series



SPECIFICATIONS

- UL Listed and CSAus.
- Qualified to ANSI C119.1-1986. CSA certified to C22.2 No. 198.2. UL 486D listed, suitable for direct burial.
- **Application:** For use on standard poly or elastomeric-insulated cables. Insulates and seals in-line compression connectors or terminal lugs. Cable can be energized immediately.

FEATURES

- Easy “roll-on” way to insulate and seal
- cable connections up to 1,000 volts.
- The gripping force of the EPDM elastomer combines with high performance sealant to form a water resistant, UV resistant insulating sleeve appropriate for direct burial application over in-line compression connectors.
- Ideal for use where gas or electric heating devices are not approved.
- RUS accepted for use as a secondary tap or splice cover.
- Each kit includes one Easy-Splice™ sleeve and sealant strips.

CAT. NO.	WIRE RANGE	CABLE O.D. (IN.)	SLEEVE LENGTH (IN.)	MAX. CONNECTOR LENGTH (IN.)	STD. CTN. QTY.
ROS-2/0	8-2/0 AWG	0.22-0.68	8.00	5.00	5
ROS-250	1/0 AWG-250 MCM	0.50-0.90	9.50	4.50	5
ROS-600	250-600 MCM	0.70-1.20	12.00	7.00	5