



BURNDY Catalog Number	GX2929
UPC Number	781810260692
Description	2/0-250 TO 2/0-250 X CON
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Width (in)	1.88
Length (in)	1.88
Height (in)	2.75
Size (Hex) or Size (Bolt)	3/8
Size (Hex) or Size (Bolt) - in	0.38
Width (Fraction)	1-7/8
Length (Fraction)	1-7/8
Height (Fraction) (in)	2-3/4
General	
Product Description	Mechanical Grounding Connector, Cable Cross Connection, 2/0 AWG (Sol.) - 250 kcmil (Run), 2/0 AWG (Sol.) - 250 kcmil (Tap), 3/8" Stud
Conductor(s)	
Copper Solid Size (Side A) - Range	2/0 AWG-4/0 AWG
Copper Str Size(Side B) - Range	1/0 -250 kcmil
Copper Str Size (Side A) - Range	1/0 -250 kcmil
CopperSolid Size (Side B) - Range	2/0 AWG-4/0 AWG
Physical	
Installation Torque	240
Type of Plating	Unplated
Plated (Yes or No)	N
Product Material	Copper Alloy
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	N
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL467
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175