

Rittal – The System.

Faster – better – everywhere.

Hygienic Design Compact enclosure HD – HD 1310.600

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygienic Design Compact enclosure HD – HD 1310.600

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	Roof slope 30° towards the front
Material:	Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel HD lock inserts: Stainless steel 1.4404 (AISI 316L) Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600
Surface finish:	Housing and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated Seal: Blue, dyed (RAL 5010)
Protection category IP to IEC 60 529:	IP 66
Protection category IP to DIN 40 050-9:	IP 69K
Protection category NEMA:	NEMA 13 NEMA 4X
Supply includes:	Housing of all-round solid construction Door with fitted seal Door catch on right, may be swapped to the left Mounting plate
Base material:	Stainless steel

Product features

Dimensions:	Height (front): 650 mm (26 ") Height (rear): 769 mm (30 ") Width: 610 mm (24 ")
--------------------	---

Depth: 210 mm (8.3 ")

Mounting plate:	Height: 570 mm (22 ") Width: 549 mm (22 ")
Number of cam locks:	2
Packaging unit:	1 pc(s).
Weight/packaging unit:	27.4 kg (60.4 lb.)
EAN:	4028177567610
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180102
Product description (long):	HD Compact enclosure, WHD: 610x650(H1)x769(H2)x210 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal
Approvals	
Approvals:	UL + C-UL
Certificates:	DGUV EAC
Declarations:	Declaration of conformity