



95-132 X 166-228 X 192-264 X 384-528 - 120/208/240  
95-132 X 166-228 X 192-264 X 384-528 Primary Volts - 120/208/240 Secondary Volts - 1Ø  
Power Conditioning - Hardwired Models



Catalog #: T169438

**PRODUCT FEATURES**

- Input range of +10/-20%
- Effective noise rejection
- UL Listed and CSA Certified
- Encapsulated transformer
- Covered under Acme's 10 year limited warranty

**BENEFITS**

- Suppressing transient spikes and surges
- Rapid response to line and load changes
- Inherent overload and short circuit protection

**UL STANDARD**

UL 1012

**CSA STANDARD**

C22.2 No. 66

**WARRANTY**

Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)

**GENERAL PRODUCT INFORMATION**

kVA:	10.00
Primary Voltage:	95-132 X 166-228 X 192-264 X 384-528
Secondary Voltage:	120/208/240
Frequency:	60 Hz
Max Temperature Rise:	115°C
UL Insulation Class:	180°C

**PRODUCT MEASUREMENTS**

Height (In./cm):	23.06 (58.6)
Width (In./cm):	27.31 (69.4)
Depth (In./cm):	24.06 (61.1)

**CONFIGURATION**

Construction Type:	Encapsulated
Mounting Type:	Floor/Wall
Wiring Diagram:	16

**PACKAGING**

Ship Weight (Lbs/Kg):	605 (274)
-----------------------	-----------

**COMPLIANCES**

UL Standard: UL 1012  
UL Listed: File E86492  
CSA Standard: C22.2 No. 66  
CSA Listed: LR7357-33  
Warranty: Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)