



# LED MR16

## 6.5MR16/F25/2700-2200 DIM 12V 10/1

Philips LED MR-16 lamps with single optic technology provide the look and color quality of traditional halogens while using a fraction of the energy. A perfect fit for spot lighting, they are compatible with most existing fixtures with MR16 GU5.3 holders and are designed as a retrofit replacement for halogen or incandescent spots.

### Product data

General Information	
Base	GU5.3 [ GU5.3]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	25000 h
Switching Cycle	50000X
Technical Type	6.5-35W
Light Technical	
Color Code	822-827 [ tunable warm white]
Beam Angle (Nom)	25°
Initial lumen (Nom)	410 lm
Luminous Intensity (Nom)	1800 cd
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	63.08 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	370 lm
Operating and Electrical	
Input Frequency	50 to 60 Hz


Power (Rated) (Nom)	6.5 W
Lamp Current (Nom)	800 mA
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	12 V
Temperature	
T-Case Maximum (Nom)	80 °C
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	- kWh
Product Data	
Order product name	6.5MR16/F25/2700-2200 DIM 12V
EAN/UPC - Product	046677454531
Order code	454538

## LED MR16

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001127804

Net Weight (Piece)	0.045 kg
--------------------	----------

### Dimensional drawing



MR16 12V 7W-35W 24D 2700K GU5.3 Dimtone

Product	D	C
6.5MR16/F25/2700-2200 DIM 12V	51 mm	50 mm

### Photometric data

