

Rittal – The System.

Faster – better – everywhere.

► Blanking panel, 3 U Tool-free attachment, 482.6 mm (19") – DK 7151.305

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Blanking panel, 3 U Tool-free attachment, 482.6 mm (19") – DK 7151.305

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	The blanking panel is used to cover unused areas within the 482.6 mm (19") mounting level. Tool-free quick-release fastening allows for easy installation in any location, and removal if necessary. The consistent use of blanking panels ensures targeted ventilation in partially occupied racks.
Benefits:	Size can be adjusted as required by bending pre-marked 1 U element Each individual element is self-supporting and may therefore be combined into larger units in conjunction with other elements
Material:	Plastic Fire behavior: Self-extinguishing, as per UL 94-HB, halogen-free
Color:	RAL 9005
Supply includes:	Blanking panel, 3 U, with integral quick-fastening

Product features

Dimensions:	Width: 482.6 mm (19 ") Width: 19"
Build height:	3 U (3 U)
Packaging unit:	3 pc(s).
Weight/packaging unit:	1.16 kg (2.6 lb.)

EAN:	4028177709263
Customs tariff number:	39269097
ETIM 6.0:	EC000456
ETIM 5.0:	EC000456
eCl@ss 8.0/8.1:	27189217
eCl@ss 7.0/7.1:	27181001
eCl@ss 6.0/6.1:	27181001
eCl@ss 5.1/5.1.4:	27182504
Product description (long):	DK Blanking panel, 482.6 mm (19"), 3 U, Toolless fixing, RAL 9005