



HOSPITAL GRADE SINGLE RECEPTACLES TAMPER RESISTANT, BACK & SIDE WIRE, 20A, 125V, RED

TR8301RED | [Pass & Seymour](#)

FEATURES & BENEFITS

These single receptacles feature durable, triple-wipe, single-piece, brass contacts and heavy-gauge steel straps, plated for enhanced corrosion resistance. Strap locks into the receptacle body to prevent pull-outs, and each features a ground clip for automatic ground connection to metal boxes. Screw-pressure-plate back wiring speeds installation and enables optional side wiring.

For detailed Tamper-Resistant receptacle information, visit our [Tamper-Resistant Receptacles](#) page.



- **.032 inch thick, brass, triple-wipe power contacts** for lasting retention.
- **Tri-drive steel terminal screws. Internal screw-pressure-plate back and side wire capability.** Two back wire holes for more wiring flexibility.
- **Dual mechanical shutter system** to help prevent insertion of foreign objects.
- **Heavy-duty, zinc-plated steel strap** for added strength.
- **Strap tabs wrap around face** to prevent strap from separating from face and back body.
- **Two drive screws anchor strap to back body and face** where abrupt removal torque is strongest.
- **Auto-ground** eliminates the necessity to terminate grounding conductor to device
- For covering patents, see www.legrand.us/patents.
- For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click [here](#).

SPECIFICATIONS

GENERAL INFO

Color: Red

Type: Single Receptacles

Special Features: Back, Side Wire

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes
CSA Standard: Yes
cUL Standard: Yes
cURus: No
Federal Spec: Yes
UL Listing No: UL498
UL Standard: Yes

DIMENSIONS

Depth (US): 1.093"
Height (US): 3.28"
Width (US): 1.32"

TECHNICAL INFORMATION

Amps: 20A
NEMA Rating: 5-20R
Volts: 125V
Volts (AC): 125
Capacity: Single
Grade Type: Hospital

BUY AMERICAN ACT COMPLIANCE

Country Of Origin: MEXICO
Buy American Act Status: Trade Agreement Act Compliant

