



MasterColor CDM ED17 Protected

MHC150/U/MP/4K ALTO 12PK

Direct retrofit with immediate energy savings! Range of protected, high-efficiency long life ceramic metal halide lamps with a stable color over lifetime and a crisp, sparkling light to be used in open fixtures.

Product data

General Information		
Base	E26 [Single Contact Medium Screw]	
Operating Position	Universal [Universal]	
Main Application	General Lighting (G)	
Life to 50% Failures (Min)	20000 h	
ANSI Code HID	C142/O	
Features	ALTO® + FadeBlock™	
Footnotes HID 1	Exclusive to Philips Lighting Company.	
Light Technical		
Color Code	940 [CCT of 4000K]	
Luminous Flux (Rated) (Min)	11000 lm	
Luminous Flux (Rated) (Nom)	12000 lm	
Color Designation	Deluxe Cool White	
Lumen Maintenance - 40% Life	75 %	
Lumen Maintenance - 10% Life	87 %	
Design Mean Lumens	9000 lm	
Chromaticity Coordinate X (Max)	0.387	
Chromaticity Coordinate X (Min)	0.369	
Chromaticity Coordinate X (Nom)	0.378	
Chromaticity Coordinate Y (Max)	0.372	

Chromaticity Coordinate Y (Min)	0.360
Chromaticity Coordinate Y (Nom)	0.366
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (Rated) (Min)	73 lm/W
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Min)	87
Color Rendering Index (Nom)	90
Operating and Electrical	
Lamp Current (Nom)	1.8 A
Ignition Supply Voltage (Min)	235 V
Re-Ignition Time (Min) (Max)	12 min
Ignition Time (Max)	10 s
Voltage (Max)	105 V
Voltage (Min)	85 V
Voltage (Nom)	95 V
Mechanical and Housing	
Bulb Finish	Clear
Cap-Base Information	Brass [Brass Cap]
·	


Datasheet, 2020, March 19 data subject to change

MasterColor CDM ED17 Protected

Bulb Material	Hard Glass
Approval and Application	
Picogram Per Lumen Hour	63.3 pg/lm.h
Mercury (Hg) Content (Nom)	12.3 mg
UV	
Pet (Niosh) (Nom)	304 h.klx
Damage Factor D/fc (Nom)	0.281
Luminaire Design Requirements	
Bulb Temperature (Max)	400 °C

190 °C
MHC150/U/MP/4K ALTO 12PK
046677377243
377242
1
12
928601171701
0.070 kg


Dimensional drawing



Product	D	C (max)
MHC150/U/MP/4K ALTO 12PK	2.125 in	5.438 in

MHC P 150W/940 E26 ED17P U ALTO+FB

Lifetime



LDLE_D-MHC-P_0002-Life expectancy diagram

MasterColor CDM ED17 Protected



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.