

Article Number: 596-00498

Solar Label, Warning- Grounded Conductors Energized Label, 4.12" X 2.0", Vinyl, Orange/White, 50/RL



Base Data

Local Order Number	596-00498
Type	WGCME
Color	Orange (OG)
Features and Benefits	<ul style="list-style-type: none">• Pre-Printed Solar Labels are made using high performance UV stable materials and adhesives for long outdoor life.• Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.• Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.• The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.
Color of Print	Black (BK)
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	4.12" X2" Black text on an Orange/White background that reads as: "WARNING - ELECTRICAL SHOCK HAZARD. IF GROUND FAULT IS INDICATED, NORMALLY GROUNDED CONDUCTORS MAY BE UNGROUNDED AND ENERGIZED" - 50 per roll.
Short Description	Solar Label, Warning- Grounded Conductors Energized Label, 4.12" X2.0", Vinyl, Orange/White, 50/RL

Product Dimensions

Width W (imperial)	4.12 "
Width W (metric)	104.6 mm
Height H (imperial)	2.0 "
Height H (metric)	50.8 mm

Logistics and Packaging

Quantity per	roll
Package Quantity (imperial)	50
Package Quantity	50

Material and Specifications

Material	Vinyl
Material Shortcut	Vinyl
Adhesive	Acrylic
Shortcut Adhesive	Acryl

Adhesive Operating Temperature	-40 °F to +174 °F (-40 °C to +79 °C)
Halogenfree	Yes
Operating Temperature	-40 °F to +174 °F (-40 °C to +79 °C)
ROHS Conformity	Yes
UL Recognized (US)	Yes