



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA36L2NTCFX  
 7818100213477  
 HYLUG 450 MCM(NOM) FLEX-  
 Active

**Web Use**  
 BURNDY Product Line

#### Dimensional

Tongue Angle  
 Length (in)  
 Tongue Type  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 E - in  
 Strip Length

Straight  
 5.24  
 Standard  
 Chamfered  
 0.52  
 Standard  
 0.27  
 1.38  
 1.74  
 1.75  
 1-3/8

#### General

Number of Holes  
  
 Product Description

2  
 Copper Compression Lug, 2 Hole  
 w/ Inspection Window, 444.4 Flex,  
 1/2" Stud, 1-3/4" Stud Hole  
 Spacing, Short Barrel, Tin Plated

#### Conductor(s)

Flex (Class G) Size - Range  
 Flex (Class H) Size - Range  
 Flex (Class I) Size - Range  
 Copper Solid Size (Range)  
 DLO Size (Range)  
 Copper Stranded (Range)

450 kcmil  
 450 kcmil  
 450 kcmil  
 N/A  
 444.4 (1100/#24) DLO  
 N/A

#### Physical

Type of Plating  
 Bolt Hole Size  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

Tin  
 1/2  
 Brown  
 Y  
 20,299  
 Copper

#### Approvals / Certifications

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS

Y  
 Y  
 Compliant  
 N  
 N

#### Documentation

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175