


Telecom Main Grounding Busbar – TMGBA24L33PT



- Meets TIA-607-C and conforms to BICSI® recommendations
- Complies with NEMA® standards
- Accepts two hole lugs with 5/16" or 7/16" bolt holes (hardware not included)
- Telecom grounding busbar splice kits are available to extend the length of the busbar



Part Number	TMGBA24L33PT
Material	Copper
Tin Plating	Yes
Width (W)	4"
Thickness (T)	1/4"
Length 1 (L1)	24"
Length 2 (L2)	18"
Hole Size 1 (HS1)	5/16"
Hole Size 1 Number of Pairs	33
Hole Size 2 (HS2)	7/16"
Hole Size 2 Number of Pairs	5
A	1"
B	1 1/8"
C	5/8"
D	5/8"
Certifications	cULus
Standard Packaging Quantity	1 pc
UPC	78285668647
EAN-13	0782856686477

BICSI is a registered service mark of Building Industry Consulting Service International, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.