

## APPLICATIONS



Ideal for **7 Day** control: Lighting, signs, pumps, motors, fans, heating & air-conditioning, security systems.



## FEATURES

- **AUTOMATIC** input voltage detection
- 7 ON and OFF pairs for programs on each day of the week
- Daylight Savings: Quick button for one hour adjustment
- Power Outage Backup:
- **BATTERY RETAINS TIME** and schedule
- **4-in-1** DPDT Contacts – include SPST, SPDT, DPST
- **LED INDICATORS** – Red for load status, Green for power
- 40 AMP contact
- Manual Override ON & OFF

## SPECIFICATIONS

### MULTI-VOLTAGE INPUT:

120/208-240/277VAC (automatic detection)

### OPERATING TEMPERATURE:

-31 °F to 116 °F (-35 °C to 47 °C)

### ENCLOSURE:

Indoor/Outdoor NEMA 3R plastic



Avoid utility peak rates  
Turn off when not needed

# DTU40

UNIVERSAL MULTI-VOLTAGE  
**24 HOUR OR 7 DAY  
DIGITAL TIME SWITCH**  
PATENT PENDING

**ACCURATE  
TO THE  
MINUTE!**

**DETECTS INPUT  
VOLTAGE  
AUTOMATICALLY!**



## RATINGS

### NO CONTACTS:

40A Resistive @ 120-277VAC  
30A Inductive @ 120-277VAC  
1HP, 30FLA, 90LRA @ 120VAC  
2HP, 20FLA, 60LRA @ 240VAC  
30A Ballast @ 120VAC  
20A Ballast @ 277VAC  
15A Tungsten @ 120VAC  
20A @ 28VDC  
720VA Pilot Duty @ 120-240VAC  
30A Max above 104 °F

### NC CONTACTS:

30A Resistive @ 120-277VAC  
15A Inductive @ 120-277VAC  
1/4HP, 12 FLA, 30LRA @ 120VAC  
1/2HP, 12FLA, 33LRA @ 240VAC  
10A Ballast @ 120-277VAC  
290VA Pilot Duty @ 120VAC  
360VA Pilot Duty @ 240VAC