



Ground Rod Clamp, Rod to Conductor, Bronze – HDC34SP



- For use with copper-bonded ground rods
- Parts that are UL Listed are suitable for direct burial in earth or concrete



Part Number	HDC34SP
Torque [TQ]	150 – 450 in lb
Material	Silicon Bronze
Ground Rod Diameter, Nominal	3/4"
Ground Rod Diameter, Actual (Ø)	0.68"
Conductor Size	#8 Solid - 3/0 Stranded 10 mm ² Solid - 70 mm ² Stranded
Wrench Size	9/16"
Certifications	CSA 46866
Standard Packaging Quantity	50 pc
UPC	78285630590

CSA, CSA-US and C-CSA-US are registered trademarks of Canadian Standards Association.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.