

SEE NOTES

REPAIRABLE



NON-REPAIRABLE



B

M-12334

1

LIST OF PARTS

DESCRIPTION	MATERIAL	FINISH
ENCLOSURE & HARDWARE	STAINLESS STEEL	
HANDLE & MOUNT	PBT	
GASKET	EPDM FOAM	
CONDUIT HUB SEAL	ZINC PLATED STEEL & NEOPRENE	

2	ADDED SEAL PER DCN #18488	TLS	1/9/12
1	RELEASED PER DCN# 19082 MAM	TLS	10/18/12
SYM	DESCRIPTION	APPROVED	DATE


THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT NOTICE

TITLE
MOTORQUICK™ LINKOSITY™ STAINLESS STEEL ENCL. TYPE 4 CIRCUIT-LOCK™ 30 AMP DISCONNECT SWITCH, POWER OUT PIGTAIL

TOLERANCES UNLESS OTHERWISE SPECIFIED		WIRING DEVICE-KELLEMS HUBBELL INCORPORATED SHELTON, CT	
FRACTIONS	±1/64	DR. BY	MAM
DECIMALS	±.005	APP. BY	TLS
ANGLES	±2°	TR. BY	MAM
		CHK'D BY	MJZ
		SCALE	NONE
		DATE	10/18/2012

M-12334

1




DRILL SPOTS FOR 3/4" NPT CONDUIT FITTING, (5) PLACES. PROVISION FOR TOP, BOTTOM, & BACK FEED. INSTALLER TO DRILL OR PUNCH Ø1.11 INCH (Ø28.2 mm) HOLE FOR CONDUIT FITTING.

LOCKABLE SWITCH HANDLE (OFF POSITION ONLY)


SEAL

30A 600V A.C. RATINGS	
HP	VOLTAGE
1 HP	120V AC 1 Ø
3 HP	200-240V AC 1 Ø
5 HP	480V AC 1 Ø
7.5 HP	200-240V AC 3 Ø
15 HP	480V AC 3 Ø
15 HP	600V AC 3 Ø

3/4 INCH NPT CONDUIT FITTING, (1) INCLUDED.



HOLES ACCEPT 1/4" DIA SCREWS MAX



- NOTES:
1. DIMENSIONS SHOWN ARE IN INCHES [mm].
2. ENCLOSURE TYPE 4X & 12.
3. CULUS LISTED.

30A 600V A.C. RATINGS		
CATALOG #	TERM. MAX. CAP. & #10 AWG Cu WIRE ONLY	TERMINAL TORQUE
HBLDS3SSMQ5		12 in-lbs [1.5 Nm]