

Rittal – The System.

Faster – better – everywhere.

Baying systems TS 8 Single – TS 8025.500

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Baying systems TS 8 Single – TS 8025.500

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Material:	Enclosure frame: Carbon steel, 1.5 mm Roof: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
Supply includes:	Enclosure frame with door Roof plate Rear panel, detachable 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting plate

Product features

Dimensions:	Height: 2200 mm (87 ") Width: 1000 mm (39 ") Depth: 500 mm (20 ")
--------------------	---

Number of doors: 1

Packaging unit: 1 pc(s).

Weight/packaging unit: 150 kg (330.7 lb.)

EAN: 751

Approvals

Approvals: Bureau Veritas
CSA
DNV-GL
Russian Maritime Register of Shipping
TÜV UL + C-UL
