

8000 SERIES

MULTIPLE ON/OFF CYCLES
REPEATING VARIABLE CYCLE
TIME SWITCH



SPECIFICATIONS

- INPUT VOLTAGE:** 120VAC, 60Hz.
TIMING ACCURACY: Line frequency.
TERMINAL RANGE: #8 - #14AWG.
OPERATING TEMPERATURE:
 -40° to 165°F (-40° to +74°C).
POWER CONSUMPTION:
 3 watts maximum.
ENCLOSURE: Indoor NEMA 1 Metal
 with lockable hasp (See pages 589-593
 for dimensions).

APPLICATIONS



- Duty cycling
 - Ventilating fans
 - Pumping
 - Irrigation
 - Process control
 - Laboratory experiments
- For one or many daily ON/OFF operations.

FEATURES

- SCHEDULING:** 60 captive tabs per dial with minimum ON/OFF settings:
- 60 minute dial with 1 minute tabs.
 - 30 minute dial with 30 second tabs.
 - 12 minute dial with 12 second tabs.
- DUTY CYCLE:** Settings of 1/60 th of dial speed.
- STANDARDS:** Listed UL917.

CAT. NO.	UPC CODE	INPUT SUPPLY (VAC) 60Hz	OUTPUT CONTACTS	TYPE
8601	70034	120	SPDT	60 Minute
8301	70033	120	SPDT	30 Minute
8121	70032	120	SPDT	12 Minute
Replacement Motor	For 8601 #102, for 8301 #108, for 8121 #107, and for 8061 #105.			

TYPE	VOLTAGE (VAC)	CONTACT RATING
Resistive	120 or 240	20A
	480	20A
Motor	120	3/4 HP

FOR MORE TIMING CHOICES SEE ELECTRONIC EJMT WITH 960 TIMING COMBINATIONS ON PAGES 513-514

ALL SPDT MODELS

