



BURNDY Catalog Number	BISR4DB
UPC Number	781810288054
Description	#4-6 DIRECTBURIAL UNITAP
Status	Active

Web Use  
BURNDY Product Line

Dimensional	
Screw Size	1/4
Width (in)	.68
Hex Size (Key)	1/8
Length (in)	4.30
Height (in)	1.39
Electrical	
Min Voltage Rating	600
General	
Number of Ports	2
Number of Screws	2
Product Description	In-Line Splice/Reducer, 2 Port, 6-4 AWG, Al/Cu Rated
Conductor(s)	
Aluminum Size (Range)	6 AWG-4 AWG
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	#6 AWG-#4 AWG
Physical	
Type of Hardware	Aluminum
Installation Torque	50
Type of Plating	Unplated
Insulation Type	Plastisol
Plated (Yes or No)	N
Product Material	Aluminum
Approvals / Certifications	
UL Listed	Y
CSA Certified	N
Rated for Direct Burial	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA  
47, industrial Park Drive  
Manchester NH03109

BURNDY Technical Servcies  
47, industrial Park Drive  
Manchester NH03109

Hours: 8.00 AM - 5.00 PM  
Monday - Friday  
Phone: 000-346-4175