


Malleable

Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 4-7/8

Dimension B in Inches: 1

Dimension C in Inches: 3-7/8

Application

Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum alloy 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.

Product Information

Material: Malleable Iron

Finish: Zinc electro-plate. Grounding lug: Tin electro-plate

Certifications & Codes:

Federal Specification Number: A-A-50553

NEMA Standard: FB-1

UL File Number: E20412

UL Standard: UL-514B

UNSPSC: 39121312

Catalog ID: 390-40

UPC Number: 781747039040

Description: Bushing, Insulated, Grounding, Malleable Iron, Size 4 Inch, 6-250 MCM Lug

Application: Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum alloy 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.

Trade Size: 4"

Country of Manufacture: USA

Std Pkg Qty: 20

Unit Qty: Bulk