



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA34LTC38FX  
7818101346588  
CULUG 350 FLEX 3/8 STUD  
Active

**Web Use**  
BURNDY Product Line

Tongue Angle  
Length (in)  
Barrell Style  
Bolt Hole Size (in)  
Barrel Type  
Thickness  
B Length (in)  
Pad Width (in)  
Strip Length

**Dimensional**

Straight  
2.87  
Chamfered  
0.39  
Standard  
0.23  
1.27  
1.55  
1-5/16

Number of Holes  
Product Description

**General**

1  
Copper Compression Lug, 1 Hole  
w/ Inspection Window, 350 Flex,  
3/8" Stud, Short Barrel, Tin Plated

Flex (Class G) Size - Range  
Flex (Class H) Size - Range  
Flex (Class I) Size - Range  
Copper Solid Size (Range)  
DLO Size (Range)  
Copper Stranded (Range)

**Conductor(s)**

350 kcmil  
350 kcmil  
350 kcmil  
N/A  
373.7 (925/#24) DLO  
N/A

Type of Plating  
Bolt Hole Size  
Color Code  
Plated (Yes or No)  
Index Number  
Product Material

**Physical**

Tin  
3/8  
Blue  
Y  
19,470  
Copper

UL Listed  
CSA Certified  
ROHS Compatible  
UL Recognized  
CULUS

**Approvals / Certifications**

Y  
Y  
Compliant  
N  
N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
Monday - Friday  
Phone: 800-346-4175