



# Eaton General purpose ventilated transformer

### V48M47T7516CU

UPC:786680178351

#### **Dimensions:**

Height: 43 INLength: 24 INWidth: 30.5 IN

Weight:504 LB

Notes:10 CFR Part 431 (2016) Efficient

#### Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

## **Specifications:**

Special Features: Fungus-resistent varnished core and coil

Type: Energy-efficient ventilated type DT-3 transformer

• Coil Material: Copper

• Efficiency: 10 CFR Part 431-2016 (DOE 2016)

• Enclosure: NEMA 2

• Frequency Rating: 60 Hz

Insulation: 220°CKva Rating: 75 kVA

• Mounting: Floor or wall, upright only

Phase: Three-phase

• Primary Voltage: 480 V

• Secondary Voltage: 480Y/277 V

• Sound Level: NEMA ST-20

Tap Size: 2 at +2.5%, 4 at -2.5%
Temperature Rise: 150 °C rise

• Voltage Rating: 480 Vac-480Y/277 Vac



# **Supporting documents:**

• Eaton Specification Sheet - V48M47T7516CU

**Certifications:** No Data

Product compliance: No Data

© 2016 Eaton. All rights reserved.