

Rittal – The System.

Faster – better – everywhere.

Captive nut – EL 2094.500

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Captive nut – EL 2094.500

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Description:	To fasten slide-in electronic equipment, 482.6 mm (19") installed equipment and blanking plates to profile rails. Used with profile plate thicknesses 0.8 – 2.0 mm. For narrow tolerances, captive nuts for profile plate thicknesses 1.2 – 1.5 mm should be used. Either with or without contacting the installed equipment with the 482.6 mm (19") profile/housing.
---------------------	---

Product features

Thread:	Type: M5
For plate thicknesses:	0,8 mm - 2 mm
Packaging unit:	50 pc(s).
Weight/packaging unit:	0.2 kg (0.4 lb.)
EAN:	4028177187351
Customs tariff number:	73181692
ETIM 6.0:	EC002358
ETIM 5.0:	EC002358
eCl@ss 8.0/8.1:	23110815
eCl@ss 7.0/7.1:	27182590

eCl@ss 6.0/6.1:	27182590
eCl@ss 5.1/5.1.4:	27182504
Product description (long):	EL Captive nuts, M5, With contact, For metal thickness: 0,8-2 mm