


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



- NOTES:
1. CATEGORY 6A UTP 28AWG CATEGORY 6A PATCH CORDS
  2. c(UL)us LISTED, FILE NUMBER E129886
  3. TERMINATED WITH (8 POSITION) MODULAR PLUGS AT BOTH ENDS PER T568B.
  4. CONSTRUCTED WITH 28AWG SOLID CONDUCTOR CATEGORY 6A F/UTP HALOGEN FREE (CM/LSZH) PATCH CABLE
  5. MATERIALS:  
PLUG: POLYCARBONATE  
CONTACTS: GOLD PLATED PHOSPHOR BRONZE
  6. NOMINAL CABLE DIAMETER IS 0.185IN (4.7MM).
  7. ALL MATERIALS AND COMPONENTS USED MUST MEET THE MATERIALS RESTRICTIONS OF RoHS, (EUROPEAN DIRECTIVE 2011/65/EU ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.
  8. 100% FACTORY TESTED FOR CATEGORY 6A PATCH CORD PERFORMANCE
  9. USE 28AWG CAT6A JACK (CJT6X88TG\*\*) FOR FIELD TERMINATION.

T568B WIRING SCHEME

PLUG POSITION	CABLE WIRE
1	WHITE ORANGE
2	ORANGE
3	WHITE GREEN
4	BLUE
5	WHITE BLUE
6	GREEN
7	WHITE BROWN
8	BROWN

CABLE COLORS	** = COLOR
OFF WHITE	--
BLACK	BL
BLUE	BU
RED	RD
YELLOW	YL
GREEN	GR
ORANGE	OR
VIOLET	VL
GREY	GY

SEE SHEET 2 FOR PATCH CORD LENGTHS AND PART NUMBERS

PART NUMBER UTP28XAAAY**	PRODUCT SPEC/PKG SPEC N/A				
I.T. NUMBER N/A	WORK INSTRUCTION N/A				
TITLE <b>CATEGORY 6A UTP 28AWG COPPER PATCH CORDS (CM/LSZH)</b> CUSTOMER DRAWING					
ITEM REVISION NAME 13M465AE/00					
DATASET FILE NAME 13M465AE_DC02/00B					
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .x ± .06 [ 1.5 ]      .xxx ± .010 [ .3 ] .xx ±      ANGLES ±					
MATERIAL: SEE NOTE 5					
DRAWING NUMBER: 13M465AE-02					
DRAWN BY BJN	DATE 11-20-14	CHK DCS	SCALE NONE	SHT 1 OF 2	SIZE A

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
1	12-29-15	BJN	DCS	TMBA	A. CORRECTED PART NUMBER	13M465AE-02
R	11-20-14	BJN	BJBE /DCS	FMS	RELEASED TO PRODUCTION	13M465AE-02

D10100DA/14

2

1

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

CATEGORY 6A UTP 28AWG PATCH CORDS

A

PANDUIT PART NUMBER	MIN. CABLE LENGTH
UTP28X3Y**	3 FEET
UTP28X5Y**	5 FEET
UTP28X7Y**	7 FEET
UTP28X10Y**	10 FEET
UTP28X14Y**	14 FEET
UTP28X20Y**	20 FEET
UTP28X1MY**	1 METER
UTP28X1.5MY**	1.5 METER
UTP28X2MY**	2 METER
UTP28X3MY**	3 METER
UTP28X5MY**	5 METER

B

B

PART NUMBER UTP28X $\Delta$ Y** $\Delta$		PRODUCT SPEC/PKG SPEC N/A	
I.I. NUMBER N/A		WORK INSTRUCTION N/A	
TITLE CATEGORY 6A UTP 28AWG COPPER PATCH CORDS (CM/LSZH) CUSTOMER DRAWING			
ITEM REVISION NAME 13M465AE/00		<b>PANDUIT</b>	
DATASET FILE NAME 13M465AE_DC02/00B			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ] .x $\pm$ .06 [ 1.5 ]      .xxx $\pm$ .010 [ .3 ] .xx $\pm$ ANGLES $\pm$		MATERIAL:	
DRAWN BY BJN		DRAWING NUMBER: 13M465AE-02	
DATE 11-20-14	CHK DCS	SCALE NONE	SIZE A

A

A

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
1	12-29-15	BJN	DCS	TMBSA	SEE SHEET 1 FOR REVISION HISTORY	13M465AE-02
R	11-20-14	BJN	BJBE/DCS	FMS	SEE SHEET 1 FOR REVISION HISTORY	13M465AE-02

2

1

D10100DA/14