

Rittal – The System.

Faster – better – everywhere.

► Air/Water Heat Exchangers wall-mounted – SK 3212.115

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Air/Water Heat Exchangers wall-mounted – SK 3212.115

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Version:	Water-carrying parts copper/brass (Cu/CuZn)
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Supply includes:	Wired ready for connection (plug-in terminal strip) Drilling template Sealing and assembly components
Note on Model No.:	Delivery times on request.

Product features

Total cooling output:	L 35 W 10 at 200 l/h: 0.3 kW (1023 BTU)
Air throughput (unimpeded air flow):	Internal circuit at 50 Hz: 260 m³/h (153 cfm) Internal circuit at 60 Hz: 300 m³/h (176.6 cfm)
Rated operating voltage:	115 V, 1~, 50 Hz/60 Hz
Dimensions:	Height: 300 mm (12 ") Width: 150 mm (5.9 ") Depth: 85 mm (3.3 ")
Temperature range:	Operation (environment): +1°C...+70°C Water inlet: +1°C...+30°C

Refrigerant/cooling medium:	Cooling medium: Water (see Internet for specifications)
Duty cycle:	100 %
Rated power Pel:	At 50 Hz: 26 W At 60 Hz: 30 W
Rated current (max.):	At 50 Hz: 0.23 A At 60 Hz: 0.24 A
Miniature circuit-breaker/fuse:	2 A
Permissible operating pressure (p. max.):	1 bar - 10 bar
Water connections:	$\frac{3}{8}$ " connector sleeve
Packaging unit:	1 pc(s).
Weight/packaging unit:	3.2 kg (7.1 lb.)
EAN:	4028177430945
Customs tariff number:	84158300
ETIM 6.0:	EC002515
ETIM 5.0:	EC002515
eCl@ss 8.0/8.1:	27180712
eCl@ss 7.0/7.1:	27180712
eCl@ss 6.0/6.1:	27180712
eCl@ss 5.1/5.1.4:	27180712
Product description (long):	SK Air/water heat exchanger, Wall-mounted, 0.3 kW, 115 V, 1~, 50/60 Hz, WHD: 150x300x85 mm

Approvals

Approvals:	Approval overview
Certificates:	EAC
Declarations:	Declaration of conformity