

Rittal – The System.

Faster – better – everywhere.

Cable duct for vertical TS section – TS 8800.520

Date : May 29, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Cable duct for vertical TS section – TS 8800.520

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Benefits: The cable duct fastening points are co-ordinated with the TS system hole pattern. This eliminates time-consuming drilling work that would be necessary with DIN ducts. The nominal break points of the bars are also designed in combination with the cable ducts for mounting plates. A further nominal break at the mounting plate height allows direct entry to the cable duct.

Material: Hard PVC
Flame-resistant, self-extinguishing

Color: Similar to RAL 7030

Supply includes: Cable duct with cover

Note: Can be shortened for other enclosure sizes.

Product features

Suitable for: Enclosure type: TS
Enclosure type: SE
Enclosure type: PC
Enclosure type: IW
Height: 2000 mm (79 ")

Dimensions: Height: 1800 mm (71 ")
Width: 50 mm (2 ")
Depth: 80 mm (3.1 ")

Bar width: 5.5 mm (0.22 ")

Slot width: 4.5 mm (0.18 ")

Packaging unit:	8 pc(s).
Weight/packaging unit:	10.47 kg (23.1 lb.)
EAN:	4028177233652
Customs tariff number:	39269097
ETIM 6.0:	EC000012
ETIM 5.0:	EC000012
eCl@ss 8.0/8.1:	27400703
eCl@ss 7.0/7.1:	27400703
eCl@ss 6.0/6.1:	27400703
eCl@ss 5.1/5.1.4:	27189224
Product description (long):	TS Cable duct for vertical TS section, WHD: 50x1800x80 mm
Approvals	
Certificates:	EAC