



BURNDY Catalog Number
UPC Number
Description
Status

YA8CL2TC10
 7818105035844
 CU HYLUG-8 STR-(2) 10 ST
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	1.83
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.20
Barrel Type	Standard
Thickness	0.08
B Length (in)	0.44
Pad Width (in)	0.41
E - in	0.62
Strip Length	7/16

General

Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 8 AWG/6 AWG, #10 Stud, 5/8" Stud Hole Spacing, Short Barrel, Tin - Electro Plated

Conductor(s)

Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	8 AWG

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	#10
Color Code	Red
Plated (Yes or No)	Y
Index Number	49
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175