

15A Portable GFCIs

Product description

2-pole, 3-wire grounding
15A, 120 V/AC

Features

- High-strength polycarbonate housing for durability
- Compact body design
- NEMA Type 3R rated for indoor/outdoor use
- Field wireable versions available for attachment to existing cords or equipment power supply
- Automatic and manual GFCI reset options available



GFP11M1P3



GFI11M133



GFI11MN3

15A plug series - single & tri-tap



Rating A	V/AC	NEMA	NEMA Type	Cord gauge	Plug type	Cord length	Catalog no.*	
15	120	5-15	3R	12/3 AWG	Single-tap	2' (0.61m)	□ GFP11M1P3	•
					Tri-tap	2' (0.61m)	□ GFP11M1P9	•
					Single-tap	25' (7.62m)	□ GFP11M4P3	•
					Tri-tap	25' (7.62m)	□ GFP11M4P9	•

*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".
Example: GFP11A1P3 = Automatic; GFP11M1P3 = Manual.

15A plug series - field wireable



Rating A	V/AC	NEMA	NEMA Type	Cord gauge	Plug type	Cord length	Catalog no.*	
15	120	5-15	3R	12/3 AWG	Flying leads	2' (0.61m)	□ GFP11MN3	•

*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".
Example: GFP11AN3 = Automatic; GFP11MN3 = Manual.

15A inline series - single & tri-tap



Rating A	V/AC	NEMA	NEMA Type	Cord gauge	Plug type	Cord length	Catalog no.*	
15	120	5-15	3R	12/3 AWG	Single-tap	2' (0.61m)	□ GFI11M133	•
					Tri-tap	2' (0.61m)	□ GFI11M139	•
					Single-tap	6' (1.83m)	□ GFI11M233	•
					Tri-tap	6' (1.83m)	□ GFI11M239	•
					Single-tap	25' (7.62m)	□ GFI11M433	•
					Tri-tap	25' (7.62m)	□ GFI11M439	•
					Single-tap	50' (15.24m)	□ GFI11M633	•
					Tri-tap	50' (15.24m)	□ GFI11M639	•

*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".
Example: GFI11A133 = Automatic; GFI11M133 = Manual.

15A inline series - field wireable



Rating A	V/AC	NEMA	NEMA Type	Cord gauge	Plug type	Cord length	Catalog no.*	
15	120	5-15	3R	12/3 AWG	Molded	1' (0.3m)	□ GFI11MN3	•

*Automatic reset GFCIs also available. When ordering automatic portable GFCIs replace "M" in Catalog number with "A".
Example: GFI11AN3 = Automatic; GFI11MN3 = Manual.

Material characteristics: Polycarbonate body. Temperature rating: -35°C to 66° (-31°F to 151°F).
Compliances, specifications and availability are subject to change without notice.

RoHS compliant - Page Q-32