



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Ferrule style high speed fuse links

**FWP-25A14F**

**UPC:**051712795951

### Dimensions:

- **Height:** 32 MM
- **Length:** 51 MM
- **Width:** 15 MM

**Weight:**.012 KG

### Warranties:

- Not Applicable

### Specifications:

- **Type:** FWP, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 25A
- **Voltage Rating:** 700 Vac (IEC), 800 Vdc (UL), 690 Vac (IEC)
- **Interrupt Rating:** 200 KAIC, 50 KAIC at 300 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I2T):** 49
- **Clearing (I2T):** Clearing at Rated voltage: 320
- **Minimum Melting:** 46.5I2t (A2 Sec)
- **Diameter:** 14 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** Class aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 7W
- **Mounting:** Fuse holder and blocks



- **Quantity:** 10
- **Fuse Size:** 14 x 51 mm

**Supporting documents:**

- [25AMP 700V AC FERRULE 14.3 X 50.8MM](#)

**Certifications:**

- UL Recognized
- CSA Certified

**Product compliance:**

- CE Marked
- RoHS Compliant