

Rittal – The System.

Faster – better – everywhere.

▶ TS 8 Flange Mount Disconnect Floormount Enclosure – TS 8018.809

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 8 Flange Mount Disconnect Floormount Enclosure – TS 8018.809 - TSFM636316XC

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description: Rittal's Floormount TS 8 combines the strength of unibody floormount enclosures with the flexibility of Rittal's revolutionary modular design. With its double door configuration and wide range of accessories, Rittal's Floormount TS 8 is sure to meet your UL Type 12 needs. Includes operator handle interlocking kit to securely lock most commercially available operator handles to enclosure and door latch.

Material: Enclosure frame: Carbon steel, 1.5 mm
Roof: Carbon steel, 1.5 mm
Door: Carbon steel, 2.0 mm
Rear wall: carbon steel, 1.5 mm
Mounting plate: Carbon steel, 3.0 mm

Color: RAL 7035

**Protection category
IP to IEC 60 529:** IP 55

**Protection category
NEMA:** UL Type 12

Supply includes: Enclosure frame with door(s)
Roof plate
Rear panel, detachable
4 eyebolts

Product features

Dimensions: Height: 1600 mm (63 ")
Width: 1600 mm (63 ")
Depth: 400 mm (16 ")

Packaging unit: 1 pc(s).

Weight/packaging unit: 208 kg (458.6 lb.)

EAN: 85552

Approvals

Approvals: UL + C-UL
