

PL-L Long 4-Pin Base

PL-L 50W/841/4P/RS

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum effciency and sleek design solutions are required.

Product data

General Information			
Cap-Base	2G11 [2G11]		
Life to 50% Failures (Nom)	10000 h		
System Description	Rapid Start (RS)		
Light Technical			
Color Code	841 [CCT of 4100K]		
Initial lumen (Nom)	4000 lm		
Color Designation	Cool White (CW)		
Lumen Maintenance 10000 h (Nom)	91 %		
Lumen Maintenance 2000 h (Nom)	94 %		
Lumen Maintenance 5000 h (Nom)	91 %		
Correlated Color Temperature (Nom)	4100 K		
Luminous Efficacy (rated) (Nom)	80 lm/W		
Color Rendering Index (Nom)	82		
Operating and Electrical			
Power (Rated) (Nom)	50.0 W		
Lamp Current (Nom)	0.430 A		

Voltage (Nom)	150 V			
Controls and Dimming				
Dimmable	Yes			
Machanian and Harring				
Mechanical and Housing				
Cap-Base Information	4P			
Product Data				
Order product name	PL-L 50W/841/4P/RS			
EAN/UPC - Product	046677347703			
Order code	347708			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	25			
Material Nr. (12NC)	927908508427			
Net Weight (Piece)	140.000 g			
ILCOS Code	FSD-50/40/1B-L/P-2G11			
	·			


Warnings and Safety

• Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Datasheet, 2018, July 23 data subject to change

PL-L Long 4-Pin Base

Dimensional drawing



PL-L 50W/841/4P RS

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
PL-L 50W/841/4P/RS	39.0 mm	18.0 mm	539.2 mm	565 mm	571.6 mm

